

CPS-CF


Helium-Free Cryogenic Probe Stations



The Model CPS-CF enables cost effective, stable, reliable and convenient probing of devices and circuits at very low temperatures. Built-in vibration isolation, smart thermal management, and engineered thermal expansion compensation makes this system ideally suited for a wide range of applications spanning from nanoelectronics (graphene research, molecular electronics, etc.) to space based electronics. The system uses closed-cycle refrigerator and proprietary thermal management permitting inexpensive and fast operations. Built-in vibration isolation minimizes the vibrations to industry-standard levels. Ultra-stable micro-manipulated stages permit accurate and reproducible contact of the probe tip on device features. Wide selection of the probes and wafer chucks permit applications ranging from ultraprecise, fA-scale measurements, RF measurements and many more.

Key Features

- Cost- competitive, stable, reliable, and convenient to use
- Temperature range from 4.5K to 480K (0.1K accuracy)
- Closed- cycle refrigerator for cost effective cryogen-free operations
- Characterization of up to 2" diameter sample
- DC to 67GHz measurements
- 4 micromanipulated probe arms (up to 8 available in optional configurations), with highly accurate XYZ and optionally θ adjustment
- Thermally anchored probe tips
- Temperature- controlled radiation shield
- Clear view top window (high purity quartz)
- High frequency vibration damping
- High level of customization to accommodate most exotic probing needs



Specifications :

Sample size

- Up to 50mm round

Thermal specifications

- Cryogen-free closed cycle refrigerator including cold head, compressor, chiller and required helium hoses
- **Temperature range:** 4.5K to 480K, 6.5K to 480K, 10K to 480K and more are available
- **Temperature accuracy:** 0.1K
- Thermally anchored probe arms and radiation shield
- Temperature controlled (heater) chuck
- Temperature monitoring of the chuck and probe arm
Temperature monitoring of radiation shield is optional

Vacuum

- Base pressure 1.0×10^{-5} torr standard, down to sub- 10^{-6} torr optional

Optics

- **Additional viewports:** can be added by customer request
- **Window materials:** fused silica, custom materials and coatings are available

Microscope:

- Qioptiq's Optem Zoom 70 system (4um resolution) is standard, Zoom 125 or zoom 160 system are available as options, as well as less expensive solutions
- Coaxial LED illumination
- Optional cooled shutter

Cameras:

- Digital cameras ranging from 1 megapixel to 10 megapixels. Included with the camera is software for image and video capture as well as dimension measurement capability

CPS-200-CF

www.microxact.com

Phone: 540-394-4040

Fax: 1-866-588-0908

Specifications (cont.):

Probes

- DC (coaxial or triaxial)
- RF (various)

Micromanipulators

- Various resolutions and ranges available

Cables available

- Cryogenic temperature- compatible coaxial cables
- Cryogenic temperature-compatible coaxial triaxial cable

Wafer chucks available

- Grounded
- Isolated
- Coaxial
- Triaxial

Software


- LabView-based software for computer control and monitoring of temperatures. Several temperature testing sequences are pre-programmed and custom sequences can be easily programmed by the end user

Vibration isolation

- Vibration isolation table with air damping system
- Vibration- isolating bellows

Options

- Fiber optic probes
- High level of customization to the customer needs



CPS-200-CF